


410011 ANTIVIBRANTE P



Goma compuesta NR 60°±5° shore A.
Espiga de acero cincado.
Usado como pie en maquinaria ligera.
Cp: Carga máxima a compresión (Kg).

Código	D	h	d	e	Cp
41001101510	15	10	M4	10	10
41001101015	15	15	M4	14	10
41001101610	16	10	M5	12	12
41001102010	20	10	M6	16	16
41001102015	20	15	M6	16	18
41001102020	20	20	M6	16	18
41001102025	20	25	M6	16	18
41001102030	20	30	M6	16	16
41001102515	25	15	M6	18	29
41001102520	25	20	M6	18	29
41001102525	25	25	M6	18	29
41001102530	25	30	M8	20	29
41001103010	30	10	M8	23	42
41001103015	30	15	M8	23	42
41001103020	30	20	M8	23	42
41001103025	30	25	M8	23	42
41001103030	30	30	M8	23	38
41001103040	30	40	M8	23	38
41001104020	40	20	M8	23	57
41001104030	40	30	M8	23	75
41001104035	40	35	M8	23	75
41001104040	40	40	M10	28	75
41001105020	50	20	M10	28	117
41001105030	50	30	M10	28	117
41001105040	50	40	M10	28	117
41001105045	50	45	M10	28	117
41001105050	50	50	M10	28	117
41001106020	60	20	M12	37	169
41001106030	60	30	M12	37	169
41001106040	60	40	M12	37	169
41001106050	60	50	M12	37	169
41001107525	75	25	M12	37	265
41001107540	75	40	M12	37	265
41001107550	75	50	M12	37	265
41001110040	100	40	M16	45	471
41001110050	100	50	M16	45	471
41001110080	100	80	M16	57	380